

(12) United States Patent

US 6,937,272 B1 (10) Patent No.:

Aug. 30, 2005 (45) **Date of Patent:**

(54) DISPLAY DEVICE FOR A CAMERA

Christopher R. Dance, Trumpington

Assignee: Xerox Corporation, Stamford, CT

(US)

Notice: Subject to any disclaimer, the term of this (*)

patent is extended or adjusted under 35

U.S.C. 154(b) by 887 days.

Appl. No.: 09/707,922

(22)Filed: Nov. 8, 2000

Int. Cl.⁷ H00N 5/228

(52)(58)

348/208.12, 333.01, 333.12, 333.05, 333.11, 348/231.3, 208.1; 345/158

(56)References Cited

U.S. PATENT DOCUMENTS

| 4,906,843 | Α | | 3/1990 | Jones et al 250/221 |
|-----------|----|---|---------|--------------------------|
| 4,926,269 | Α | * | 5/1990 | Takano et al 358/474 |
| 5,585,875 | A | * | 12/1996 | Imafuji et al 348/208.11 |
| 5,602,566 | A | * | 2/1997 | Motosyuku et al 345/684 |
| 5,714,972 | A | * | 2/1998 | Tanaka et al 345/156 |
| 5,748,228 | A | * | 5/1998 | Kobayashi et al 348/63 |
| 5,844,824 | A | | 12/1998 | Newman et al 364/708 |
| 5,905,525 | A | * | 5/1999 | Ishibashi et al 348/39 |
| 5,943,603 | Α | * | 8/1999 | Parulski et al 348/211.2 |
| 6,011,526 | A | | 1/2000 | Toyoshima et al 345/7 |
| 6,233,015 | B1 | * | 5/2001 | Miller et al 348/33.05 |
| 6,300,933 | B1 | * | 10/2001 | Nagasaki et al 345/685 |
| 6,411,275 | B1 | * | 6/2002 | Hedberg 348/39 |
| | | | | |

| 6,476,861 | B1 * | 11/2002 | Min | . 348/208.15 |
|-----------|------|---------|------|--------------|
| 6.552.744 | B2 * | 4/2003 | Chen | 348/218.1 |

OTHER PUBLICATIONS

Verplaetse, "Inertial Proprioceptive Devices: Self-motionsensing Toys and Tools," 1999, IBM Systems Journal, vol. 35, Nos. 3&4, 639-650.*

E. Foxlin and N. Durlach, "An Inertial Head Orientation Tracker with Automatic Drift Compensation Doe Use with HMD's," Proceedings from VRST'94, Virtual Reality Software and Technology, Singapore, Aug. 23-26, 1994. C. Verplaetse, "Inertial Proprioceptive Devices: Self-motion-sensing Toys and Tools," IBM Systems Journal, vol. 35, Nos. 3&4, 1996, pp. 639-650.

* cited by examiner

Primary Examiner—Tuan Ho Assistant Examiner—Gevell Selby

ABSTRACT

A camera is described having a display device for displaying one or more stored images after acquisition. The camera has a motion detector which enables the selection and/or display of a stored image to be controlled (at least partly) by physical movement of the camera. Scrolling (or panning) of an image in the display can be effected by moving the camera in a plane parallel to the plane of the camera display, or tilting the camera. Zooming can be effected by moving the camera is a direction generally perpendicular to the plane of the camera display. The movements are generally similar to those which the user would make if viewing the image through a window or lens, which leads to a highly intuitive manner of operation.

22 Claims, 6 Drawing Sheets

